

BATTERY OPERATED IMPACT DRILL MACHINE SHALL BE OF FOLLOWING SPECIFICATIONS/FEATURE:


CAPACITY	:	BOLT 3-8 MM(1/8 – 5/16")
		MACHINE SCREW 3-8 MM(1/8 – 5/16")
BATTERY CAPACITY	:	1.5Ah. 7.2 V (Li-ION) BATTERY
TIGHTENING TORQUE	:	25Nm-40Nm
NO LOAD SPEED	:	0-2400 RPM
FULL LOAD SPEED	:	0-3000 RPM
DRIVE	:	6.35 MM HEX BIT SHANK


MACHINE SHOULD BE CONVERTED FROM L-SHAPE TO STRAIGHT SHAPE.

MACHINE SHOULD HAVE AUTOMATIC SPINDLE LOCK MECHANISM FOR MANUAL TIGHTENING.

MACHINE SHOULD HAVE ADJUSTABLE TIGHTENING SPEED.

MACHINE SHOULD HAVE PROTECTION FOR BATTERY.

  
उपस्थायक विद्युत अभियंता  
मध्य रेलवे कारखाना, माटुंगा  
Assistant Electrical Engineer  
Central Railway Workshop  
MATUNGA

  
वरिष्ठ अनुभाग अभियंता  
विद्युत मरम्मत खाता, माटुंगा  
Senior Section Engineer  
E.R. SHOP, MATUNGA.  
Shop No. 94523

